

PERPETUAL MOTION ENERGY OF (GOD) ON GENERATING STATIONS

CROSS-REFERENCES TO RELATED APPLICATIONS

New CIP of Prior Ser. No. 08/980,485 on 02/28/97 now pending

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention refers to energy and specifically to perpetual energy, i.e., regarding generating stations and substations including perpetually define bridges. While the bridges include **PERPETUAL ENERGY (P.E.)**, their lights are to illuminate the bridges perpetually, thereby a system, as set forth in my prior **UNITED STATES Patent Number:**

Further, two several hundred ton batteries enclosed via conventional battery chargers, as set forth in my prior U.S. **Patent**, charges one another, so, as to, perpetually generate electric energy. This PE system will replace all heretofore electrical equipment, and can perpetually deliver electrical energy to associated systems, however for one hundred years.

X Department of Energy (General Provisions) (Parts 1000 1099), and XXXI Office of Environmental Quality with respect to the Department of Agriculture (Parts 3100 3199) by way of **CFR**, thus will regulate and control **PERPETUAL MOTION ENERGY. P.M.E. (PERPETUAL MOTION ENERGY)** systems will save thousands of dollars yearly, in maintenance cost for US organizations. While safety, and environmental concerns each of which is an important issue, a **P.M.E. Electrically Powered Locomotive** is to provide high **Perpetual motion energy** concerning its load. **On earth, only one nation will be generating Giant Perpetual Motion Energy Systems; namely, THE UNITED STATES OF AMERICA.**

Description of the Prior Art

PERPETUAL MOTION ENERGY is a revolutionary 21st Century reality, so that **AMERICA** do not have to depend on mechanical energy being changed into electrical energy by water, steam, gas and oil, as gasoline and petroleum. **PERPETUAL ENERGY** is a dominating power from (GOD), thus, presented to applicant, as a gift such that he will teach it under the provisions of the Code of Federal Regulations.

SUMMARY OF THE INVENTION

Accordingly, one object of this present invention is to provide perpetual energy with respect to structures, such as **Generating Stations, Bridges with Perpetual Battery Operated Phones, which turn on lights for illuminating these bridges, and Airports** regarding perpetual battery operated equipment.

However, to accomplish the foregoing and other objects, a perpetual energy system for generating stations concerning (GOD) comprises: a charging system defining two batteries in such system, a first battery to fit a first charger, whereby a second battery is sized to befit a second charger, a first DC-AC converter and a first plug to befit a first receptacle on the first charger, a second DC-AC converter, and a second plug in a second receptacle upon the second charger and ways for the batteries to load each other, a first AC adaptor and a third plug to fit a first jack upon the first charger, so, the adaptor is to fit a socket via the second converter, the second charger comprises a way for outputting AC current for charging the first battery, a second AC adaptor and a fourth plug so as to fit a second jack about the second charger, as the adaptor is to befit a socket on the first converter, the first charger comprises ways to output current to charge the second battery, circuit breaker systems for interrupting the batteries regarding power via obstructing two circuits. The charging system has two pairs of **LEDs** to indicate low charge thereby, the breaker systems are to close the circuits. The batteries having a fifth to sixth **LED** to show full, whereby, the circuits comprise a way for being opened. The batteries connected via series, and ways thereby to operate, a seventh and eight **LED** have a way to emit light. The charging system is to connect to a generator whereby the batteries have ways to work as the generator is off. The batteries thereby have nonmetallic electric conductors, one solvent to dissolve and a ninth **LED** on power. The batteries have a transmitter, and ways to be refilled, whereby, the ninth **LED** is to emit light at one hundred years.

According to another merit regarding the new invention, a perpetual energy complex of GOD comprises charging systems which adds two batteries, such that the batteries are to fit in conventional chargers, DC-AC converters for converting DC current to alternating current regarding two converters, one first, and second AC adaptor including ways for charging the batteries by the converters, a generating station system for producing perpetual energy, illumination systems for thereby illuminating the batteries having spiraled light fixtures so as to enclose lamps, an authorized person defines a scooter, and a way for replacing the lamps, elevators for maintenance thereof receptacles and plugs, and a way for plugging in the converters. The batteries thereby, include ways to load one another, an adjacent bridge having self-chargeable batteries also. The bridge has bases whereby on each side of a river, the bases comprise the self-chargeable batteries, thereinto. The bridge having lamps and a way to thereby illuminate, the batteries have ways to illuminate the bridge. The batteries thereby, include structures, a main control center comprises feeders, branch circuits and a system ground. The lamps via the bridge comprises ways to be turned on by way of a timer, conventionally. The main control center, thereby, comprises branch control centers, and ways to send perpetual energy to various parts of a City.

BRIEF DESCRIPTION OF THE DRAWINGS

Further objects and advantages given herewith about the present invention will be apparent regarding these drawings, and the preferred embodiments pertaining to the description, which should not be construed as limitations on the scope of the invention, but by the append claims;

FIG. 1 is a section view about two batteries concerning two battery chargers, which charge one another, perpetually;

FIG. 2 is a block diagram simplifying perpetual energy;

FIG. 3 is a section view defining a service entrance so as to replace flourescent lamps in a spiraled light fixture;

FIG. 4 is a perspective view via a bridge with bases on each side of a river, and has two self chargeable batteries;

FIG. 5 is a perspective view of a portion of the bridge adjacent the two battery chargers and their spiraled lights;

FIG. 6 is a rearward portion of one charger defining an electrical arrangement, so, as to transmit perpetual energy;

FIG. 7A is a diagram about a Double-bus, double circuit breaker system, comprising added assurance against shutdown;

FIG. 7B is a section view via a conventional generator;

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to **FIG. 1**, two battery chargers **H3-H4** include two batteries **B3-B4**, which charge one another as two LEDs **Rc** to **Rd** emit light on the chargers **H3-H4**.

The batteries **B3** to **B4** with respect to the conventional chargers **H3-H4**, however, are protected by reason of an inner circuit breaker so as to, automatically interrupt the power, when the current surpasses a set limitation concerning **AMPS**.

A plug **P3** of a **DC-AC converter V3** fits an output outlet **03** on the charger **H3**. A **DC-AC converter V4** has a plug **P4** in an output outlet **04** upon the charger **H4**. This system causes each **22,000 V** battery to charge each other, as an **AC adapter A3** fits a charger jack 2 by its plug **M3** upon the charger **H3**. As the adapter part **A3** plugs in the **converter V4** the battery **B4** outputs current that charges the battery **B3**. Now this is done, as an **AC adapter A4** fits a charger jack 3 by a plug **M4** on the charger **H4**, the adapter **A4** plugs in the **converter V3**.

When the **battery B3** is charging the **battery B4**, the output outlet **03** on this charger **H3** outputs **22,000 V DC** current by which the **converter V3** converts into alternating current. The current flows through this adapter **A4**, its lead, and the plug **M4** via the charger jack 3. This charges the battery **B4** whereby, the battery **B4** is likewise charging the battery **B3**. As shown in **FIG. 7A**, a block diagram is provided for showing that a double-bus, double circuit-breaker **Z1-Z2** prevents the batteries **B3-B4** from overloading as the LEDs **Rc-Rd** glow when each battery **B3-B4** charges one another. Two LEDs **Gs-Hs** glow as each battery **B3-B4** endures a full charge. As the LEDs **Gs** to **Hs**, and two LEDs **RG** and **SG** emit light, each battery **B3-B4**

should be charged. The breakers Z1 and Z2 define disconnect switches and tie-bus breakers, such as to close two circuits C3-C4. Now, each battery B3-B4 starts charging one another. The batteries B3-B4 charge each other and when a full charge is, nigh, two LEDs X-y emit light. The batteries B3-B4 load one another to sustain a full charge, even as a generator GT in a generating station is turned off, as shown in FIG. 7B.

Now, maximum flexibility is provided by the double-bus, double-breaker system as shown in FIG. 7A. This arrangement is now provided, chiefly, in large generating stations where continuity of service is of prime importance. Consequently, both batteries B3-B4 charge one another, as a full charge is shown by the LEDs X-y, the double bus, double breaker system prevents damage to the central charging circuits C3-C4. Now this is accomplished only, via the breakers Z1-Z2 concerning the disconnecting switches so as to open the circuits C3-C4.

As shown in FIG. 2, the DC-AC converter V3 is connected to the charger H3, as the DC-AC converter V4 is connected to the charger H4, each battery B3-B4 charges one another as an end of the AC adapter A3 is connected to the charger H3. As the AC adapter part A3 is plugged into the converter V4, the battery B4 outputs current that charges the battery B3. Now this is done as a lead of the adapter A4 is connected to the charger H4, since its adapter portion A4 is plugged into the converter V3. The breakers Z1-Z2 are connected via an input terminal of the converters V3-V4. The LEDs Gs-SG emit light as each battery B3-B4 requires charging, all LEDs Rc-Rd, Gs, Hs, RG, SG, X, and y are connected via the other terminal of the converters V3-V4. The LEDs X-y emit light whenever each battery B3-B4 is fully charged by (PE) perpetual energy.

The PE system outputs current for charging each battery for one hundred years. As shown in FIGS. 1, 3, and 6, a LED 100 emits light via the battery charger H3 after one hundred years, and roughly, 6 months. While this is the life of the perpetual energy system, its producing mechanism regenerates the voltage in both batteries to a, fully, charged operating level as set forth above for one hundred years. E.g., this LED 100 emits light by an AC or DC current-limiting resistor to indicate that the batteries B3-B4 should be refilled.

The generator GT, as shown in FIG. 7B does not comprise a conventional motor, seeing that this generator GT plugs in the converter V3 about the perpetual energy system shown via FIG. 1. Since the plugs GG, and HH are generator plugs, the energy system as shown in FIG. 1 is connected to two hundred generators. As shown in FIG. 5, the two converters V3 to V4 can be, clearly seen adjacent the bridge BR and its base Bs.

While the above description defines many specificities, these should not be construed as limitations on the scope of the invention, but rather, as an example about one preferred embodiment thereof. Many other variations and modifications are possible, for example, two additional receptacles can be installed concerning two batteries, such that two converters can plug in the two additional receptacles, so as to deliver additional energy perpetually to various locations of a City or, a housing development, perpetual battery operated phones without heretofore chargers, portable perpetual esculentors, so as to load and unload passengers at airports, perpetually defined portable systems for an A/C, electric-range, vehicle applications, hospitals, banks, trailer homes, ocean liners, jetliners, video equipment, musicale instruments, recorders, and systems about which perpetual energy is so needed. This witty invention should not be limited by the embodiment, but by the appended claims and their legal equivalents.